



Phoenix Lite 3

Compact Outside, Advancements Inside

Phoenix Lite 3 is a compact diagnostic scanner designed for automotive professionals, enthusiasts, and small repair shops. Tailored to meet the diverse needs of the automotive industry, Phoenix Lite 3 offers unparalleled functionality and affordability. With features like CAN-FD protocol, online coding, and topology mapping functions, it stands out as the top choice for a wide range of users.

Features

- . Supports CAN-FD protocol
- . Supports topology mapping
- . Supports Online Coding function for Audi, BMW, Porsche, and other models
- . Supports Guide function for VAG models
- . FCA gateway support for better coverage of new models and features
- . Diagnostic reports can include additional information as per user requirements, such as report type, cost, mileage, technician name, etc
- . Automatically generates diagnostic reports, which can be shared via Email, Bluetooth, and QR code in various formats
- . Supports 35 common service functions for mainstream models
- . Supports full-system diagnosis for over 160 brands and models
- . Supports Bi-directional control for active testing
- . ADAS add on

What's in the Box

Phoenix Lite 3 *1
MDCI Dongle *1
User Manual *1
Package List *1

Battery Clamps/Cable Set *1
Cigarette Lighter Cable *1
Fuse (φ5*20mm) *4

TA-17 (TOYOTA) *1
G/V-12 (GM/VAZ) *1
B-20 (BMW) *1
CR-6 (CHRYSLER) *1

HA-3 (HONDA) *1
NN-14+16 (NISSAN) *1
M/H-12+16 (MITSUBISHI/HYUNDAI) *1

FT-3 (FIAT) *1

Fuse (φ6*30mm) *2
Type-C to USB Cable *1

Power Adaptor *1

OBDI Adaptor BOX Transfer *1

OBDII Extension Cable *1

BZ-38 (BENZ) *1

TA-22 (TOYOTA) *1

Specs

Display: LCD 8-Inch, 1280 * 800

CPU 4-Core Processor, 2.0 GHz

System: Android 10.0

Storage: RAM: 2G, ROM 64G

Battery: 12600 mAh / 3.8V (24 hours lasting)

Operating voltage: 9~18V

Storage Temperature: -20°C ~ 60°C (-4°F ~ 140°F)

Working Temperature: 0°C ~ 50°C (32°F ~ 122°F)

Dimension: 258*183*50.5 mm (10.16*7.20*1.99 inch)

Package size: 468*320*143 mm (18.43*12.60*5.63 inch)

Net Weight: 1184.5 g (2.61 lb)

Multilingual Support: English, German, Spanish, French, Italian, Japanese, Portuguese, Russian, Polish, Turkish, Dutch, Hungarian, Chinese (Traditional), Korean, Greek, Slovak, Romanian, Arabic, Croatian, Slovenian, Finnish, Czech



CONTACT US

[X](#) [Instagram](#) [Facebook](#) [YouTube](#) @topdonofficial

TOPDON TECHNOLOGY Co., Ltd. | WWW.TOPDON.COM

sales@topdon.com | +86-755-21612590 +1-833-629-4832 (North America)

Unit 2005 20/F, No.3040 Xinghai Avenue, Qianhai Shimao Tower, Qianhai Shenzhen-Hong Kong Cooperation Zone, Shenzhen, P.R.China | 518000